

RG59+2DC COAXIAL CABLE (SAAT DIGITAL)

Features and Functions

- 1.305m RG59 coaxial cable with power cable
2. Conductor material of Coaxial cable is copper
3. Braiding material of Coaxial cable is CCA(Copper-clad Aluminum)
4. Conductor material of power cable is CCA(Copper-clad Aluminum)
5. VW-1 flame retardant rating
6. Excellent anti-interference performance
7. Excellent anti-aging performance



Model		RG59+2DC
Coaxial Cable		
Conductor	Material	copper
	Wire Gauge	20AWG
	Diameter	0.81±0.01mm
Insulation	Material	FPE
	Diameter	3.66±0.05mm
Tape	Material	Shielding Aluminum Foil ,14mmwidth
	Thickness	0.04mm
Braid	Material	CCA(Copper-clad Aluminum)
	BraidingStandard	6*16*0.12mm
	Braiding Density	95±1%
Jacket	Material	PVC
	AverageThickness	≥0.65mm
	Diameter	6.10±0.2mm
Impedance		75ohms
Power Cable		
Conductor	Material	CCA(Copper-clad Aluminum)
	Quantity	2
	Diameter	7*0.37±0.01mm
Insulation	Material	PE(Flame Retardant)
	Diameter	1.8±0.1mm
Jacket	Material	PVC
	Average Thickness	≥0.3mm
General		
Length		100m
Color		Black
Operating Temperature		-40-80°C
Storage Temperature		-20-70°C
Weight		17KG

Dimensions (LxWxH)	33*33*3 7CM
-----------------------	-------------

Coaxial Cable Transmission Performance	
Frequency(MHz)	Attenuation(dB/100m)
55	7.30
200	10.80
400	14.88
500	18.50
800	28.23
1000	34.70
1500	42.80
2250	52.90
3000	61.00